

HPE FlexFabric 5945 Switch Series



Key features

- Cut through with ultra-low latency and wirespeed
- These switches are NEBS certified making them the ideal fit for telecom customers (applicable for JQ074A and JQ077A)
- VXLAN, EVPN, and MPLS support for virtualized environments
- High-density 100GbE/40GbE/25GbE/10GbE spine/top-of-rack (ToR) connectivity
- PTP 1588V2 IEEE 802.1AS support for Boundary Clock, Transparent Clock, End to End/Peer to Peer Transparent Clock
- New 32G/16G FC support for storage networking and RoCE v1/v2 for RDMA high-performance computing
- IPv4 and IPv6 support with full L2 and L3 features
- Includes Distributed Resilient Network Interconnect (DRNI) offers high availability and resiliency by combining multiple physical switches into one virtual distributed-relay (DR) system
- HPE IMC Orchestrator and Analyzer to simplify network management and operations
- Greater flexibility with two/four slot options for varying use cases such as MACsec 256-bit encryption, high-performance DC leaf, storage networking with FC and NVMe storage
- **New** made in USA TAA SKUs introduced for customers who have concerns with 'made in China' products. These SKUs are provide additional security as a combination of manual and automated source code analysis is performed to identify common programming issues and address any security weaknesses.

Product overview

HPE FlexFabric 5945 Switch Series is a family of high-density, ultra-low latency, and ToR switches that is part of HPE FlexFabric solution (from the HPE Cloud-First Reference Architecture).

Ideally suited for deployment at the aggregation or server access layer of large enterprise data centers and telecom customers. The HPE FlexFabric 5945 Switch Series is also powerful enough for deployment at the core layer of medium-sized enterprises.

With the increase in virtualized applications and server-to-server traffic, customers require spine and ToR switches that can meet their throughput requirements. With the HPE FlexFabric 5945, data centers can now support up to 100 Gb per ports, allowing high-performance server connectivity and the capabilities to handle virtual environments. This is available in the low-latency HPE FlexFabric 5945 Switch Series.

Features and benefits

Quality of service (QoS)

- Powerful QoS features
 - Flexible queue scheduling
 - Including Strict Priority (SP), WRR, WFQ, SP+WRR, SP+WDRR, SP+WFQ, configurable buffer, time range, queue shaping, and CAR with 8 kbps granularity
 - Packet filtering based on packet header fields from Layer 2 through Layer 4
 - Including source MAC, destination MAC, source IP (IPv4/IPv6), destination IP (IPv4/IPv6), port number, protocol type, and VLAN

Data center optimized

- Flexible high-port density

HPE FlexFabric 5945 Switch Series enables scaling of the server edge, with 100GbE, 40GbE, 25GbE, and 10GbE spine and leaf deployment. The HPE FlexFabric 5945 Switch Series solution includes a 48-port of 25 Gb with 8-port of 100 Gb, 32-port of 100 Gb and 2 modular models of respectively 1 RU / 2-slot and 2 RU / 4-slot.
 - High-performance switching

Cut through and nonblocking architecture delivers low latency (~ 1 microsecond for 100GbE) for very demanding enterprise applications; the switch delivers high-performance switching capacity and wirespeed packet forwarding
 - Higher scalability

HPE Intelligent Resilient Fabric (IRF) technology simplifies the architecture of server access networks; up to 10 HPE FlexFabric 5945 switches can be combined to deliver unmatched scalability of virtualized access layer switches and flatter 2-tier networks using HPE IRF, which reduces cost and complexity
 - Advanced modular operating system

Comware v7 software's modular design and multiple processes bring native high stability, independent process monitoring, and restart; the OS also allows individual software modules to be upgraded for higher availability and supports enhanced serviceability functions such as hitless software upgrades with HPE IRF based in-service software upgrade (ISSU)
 - Reversible airflow

Enhanced for data center hot-cold aisle deployment with reversible airflow—for either front-to-back or back-to-front airflow
 - Redundant fans and power supplies

Internal redundant and hot-pluggable power supplies and dual fan trays enhance reliability and availability
 - Lower OpEx and greener data center Provides reversible airflow and advanced chassis power management
 - Data Center Bridging (DCB) protocols Provides support for IEEE 802.1Qbb Priority Flow Control (PFC), Data Center Bridging Exchange (DCBX), IEEE 802.1Qaz Enhanced Transmission Selection (ETS), Explicit Congestion Notification (ECN) for converged FCoE, iSCSI, and RoCE environments
 - Jumbo frames

With frame sizes of up to 9416 bytes on 100GbE ports, high-performance remote backup and disaster recovery services are enabled
 - VXLAN hardware support

VXLAN L2/L3 gateway support for up to 4K tunnels
 - Dynamic VXLAN configuration OVSDB support for dynamic VXLAN configuration
 - MACsec encryption with swappable interface modules for enhanced security
- ### Manageability
- HPE IMC Orchestrator and Analyzer offer enhanced network operations with orchestration, automation, and analytical capabilities
 - Automated network overlay/underlay deployment
 - Enhanced visibility with application telemetry
 - AI-enabled network monitoring for faster troubleshooting



– For more information, please refer to the [HPE IMC Orchestrator and Analyzer data sheet](#)

- Full-featured console

Provides complete control of the switch with a familiar CLI

- Troubleshooting

– Ingress and egress port monitoring

Enables network problem solving

– Traceroute and ping

Enables testing of network connectivity

- Multiple configuration files

Allows multiple configuration files to be stored to a flash image

- sFlow® (RFC 3176)

Provides wirespeed traffic accounting and monitoring

- SNMPv1, v2c, and v3

Facilitates centralized discovery, monitoring, and secure management of networking devices

- Out-of-band interface

Isolates management traffic from user data plane traffic for complete isolation and total reachability, no matter what happens in the data plane

- Remote configuration and management

Delivered through a secure CLI over Telnet and SSH; role-based access control (RBAC) provides multiple levels of access; configuration rollback and multiple configurations on the flash provide ease of operation; remote visibility is provided with sFlow and SNMPv1/v2/v3, and is fully supported in [HPE Intelligent Management Center \(IMC\)](#)

- ISSU and hot patching

Provides hitless software upgrades with IRF-based ISSU and hitless patching of the modular operating system

- PTP and NTP support

Synchronizes timekeeping among distributed time servers and clients; support for Precision Time Protocol (PTP) and Network Time Protocol (NTP)

Resiliency and high availability

- IRF technology

Enables an HPE FlexFabric switch to deliver resilient, scalable, and secured data center networks for physical and virtualized environments; groups up to 10 HPE FlexFabric 5945 switches in an HPE IRF configuration, allowing them to be configured and managed as a single switch with a single IP address; simplifies ToR deployment and management, reducing data center deployment and operating expenses

- IEEE 802.1w Rapid Convergence Spanning Tree Protocol (STP)

Increases network uptime through faster recovery from failed links

- IEEE 802.1s Multiple Spanning Tree Provides high-link availability in multiple VLAN environments by allowing Multiple Spanning Trees

- Virtual Router Redundancy Protocol (VRRP)

Allows groups of two routers to back each other up dynamically to create highly available routed environments

- Hitless patch upgrades

Allows patches and new service features to be installed without restarting the equipment, increasing network uptime, and facilitating maintenance

- Fast protocol convergence with standard-based failure detection—Bidirectional Forwarding Detection (BFD)

Enables link connectivity monitoring and reduces network convergence time for RIP, OSPF, Border Gateway Protocol (BGP), intermediate system to intermediate system (IS-IS), VRRP, MPLS, and IRF



- Device Link Detection Protocol (DLDP)

Monitors link connectivity and shuts down ports at both ends if unidirectional traffic is detected, preventing loops in STP-based networks

- Graceful restart

Allows routers to indicate to others their capability to maintain a routing table during a temporary shutdown and significantly reduces convergence times upon recovery; supports OSPF, BGP, and IS-IS

L2 switching

- Address Resolution Protocol (ARP)

Supports static, dynamic, and reverse ARP and ARP proxy

- IEEE 802.3x Flow Control

Provides intelligent congestion management via PAUSE frames

- Ethernet Link Aggregation

Provides IEEE 802.3ad Link Aggregation of up to 256 groups of 32 ports; support for LACP, LACP Local Forwarding First, and LACP short-time provide a fast, resilient environment that is ideal for the data center

- Spanning Tree Protocol

Supports STP (IEEE 802.1D), Rapid STP (RSTP, IEEE 802.1w), and Multiple STP (MSTP, IEEE 802.1s)

- VLAN support

Provides support for 4096 VLANs based on port

- IGMP support

Provides support for IGMP Snooping, fast-leave, and group policy; IPv6 IGMP Snooping provides L2 optimization of multicast traffic

- DHCP support at L2

Provides full DHCP Snooping support for DHCP Snooping Option 82, DHCP Relay Option 82, DHCP Snooping Trust, and DHCP Snooping Item Backup

L3 services

- Address Resolution Protocol

Determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a L2 network

- Dynamic Host Configuration Protocol

Simplifies the management of large IP networks and supports client and server; DHCP Relay enables DHCP operation across subnets

- Operations, administration, and maintenance (OAM) support

Provides support for Connectivity Fault Management (IEEE 802.1AG) and Ethernet in the First Mile (IEEE 802.3AH); provides additional monitoring that can be used for fast fault detection and recovery

L3 routing

- EVPN and EVPN-DCI

Can act as a VTEP, EVPN Gateway, or Border Gateway enabling virtual multipoint-bridged connectivity between different Layer 2 domains over an IP network

- VRRP and VRRP Extended

Allows quick failover of router ports

- Policy-based routing

Makes routing decisions based on policies set by the network administrator

- Equal-Cost Multipath (ECMP)

Enables multiple equal-cost links in a routing environment to increase link redundancy and scale bandwidth



- L3 IPv4 routing
 - Provides routing of IPv4 at media speed; supports static routes, RIP and RIPv2, OSPF, BGP, and IS-IS
- Open shortest path first
 - Delivers faster convergence; uses this link-state routing interior gateway protocol (IGP), which supports ECMP, NSSA, and MD5 authentication for increased security and graceful restart for faster failure recovery
- Border Gateway Protocol 4
 - Delivers an implementation of the BGP utilizing path vectors; uses TCP for enhanced reliability for the route discovery process; reduces bandwidth consumption by advertising only incremental updates; supports extensive policies for increased flexibility; scales to very large networks
- Intermediate system to intermediate system
 - Uses a path vector IGP, which is defined by the ISO organization for IS-IS routing and extended by IETF RFC 1195 to operate in both TCP/IP and the OSI reference model (integrated IS-IS)
- Static IPv6 routing
 - Provides simple manually configured IPv6 routing
- Dual IP stack
 - Maintains separate stacks for IPv4 and IPv6 to ease the transition from an IPv4-only network to an IPv6-only network design
- Routing Information Protocol next generation (RIPng)
 - Extends RIPv2 to support IPv6 addressing
- OSPFv3
 - Provides OSPF support for IPv6
- BGP+
 - Extends BGP-4 to support Multiprotocol BGP (MBGP), including support for IPv6 addressing
- IS-IS for IPv6
 - Extends IS-IS to support IPv6 addressing
- IPv6 tunneling
 - Allows IPv6 packets to traverse IPv4-only networks by encapsulating the IPv6 packet into a standard IPv4 packet; supports manually configured, 6 to 4, and intra-site automatic tunnel addressing protocol (ISATAP) tunnels; is an important element for the transition from IPv4 to IPv6
- Policy routing
 - Allows custom filters for increased performance and security; supports ACLs, IP prefix, AS paths, community lists, and aggregate policies
- Bidirectional Forwarding Detection
 - Enables link connectivity monitoring and reduces network convergence time for RIP, OSPF, BGP, IS-IS, VRRP, MPLS, and IRF
- Multicast routing PIM dense and sparse modes
 - Provides robust support of multicast protocols
- L3 IPv6 routing
 - Provides routing of IPv6 at media speed; supports static routing, RIPng, OSPFv3, BGP4+ for IPv6, and IS-ISv6
- Storage Network
 - 32/16/8/4/2G Fibre Channel, FCoE, NVMe over FC, RoCE v1/v2. VMware vSAN™ and Zoning, single and multi-hop SAN network.



Additional information

- Green IT and power

Improves energy efficiency through the use of the latest advances in silicon development; shuts off unused ports and utilizes variable-speed fans, reducing energy costs

Management**USB support**

- File copy

Allows users to copy switch files to and from a USB flash drive

- Multiple configuration files

Stores easily to the flash image

- SNMPv1, v2c, and v3

Facilitates centralized discovery, monitoring, and secure management of networking devices

- Out-of-band interface

Isolates management traffic from user data plane traffic for complete isolation and total reachability, no matter what happens in the data plane

- Port mirroring

Enables traffic on a port to be simultaneously sent to a network analyzer for monitoring

- Remote configuration and management is available through a CLI

- IEEE 802.1AB Link Layer Discovery Protocol (LLDP)

Advertises and receives management information from adjacent devices on a network, facilitating easy mapping by network management applications

- sFlow (RFC 3176)

Provides scalable ASIC-based wirespeed network monitoring and accounting with no impact on network performance; this allows network operators to gather a variety of sophisticated network statistics and information for capacity planning and real-time network monitoring purposes

- Command authorization

Leverages RADIUS to link a custom list of CLI commands to an individual network administrator's login; an audit trail documents activity

- Dual flash images

Provides independent primary and secondary operating system files for backup while upgrading

- Command-line interface

Provides a secure, easy-to-use CLI for configuring the module via SSH or a switch console; provides direct real-time session visibility

- Logging

Provides local and remote logging of events via SNMP (v2c and v3) and syslog; provides log throttling and log filtering to reduce the number of log events generated

- Management interface control

Provides management access through a modem port and terminal interface, as well as in-band and out-of-band Ethernet ports; provides access through terminal interface, Telnet, or SSH

- Industry-standard CLI with a hierarchical structure

Reduces training time and expenses, and increases productivity in multivendor installations

- Management security

Restricts access to critical configuration commands; offers multiple privilege levels with password protection; ACLs provide Telnet and SNMP access; local and remote syslog capabilities allow logging of all access



- Information center

Provides a central repository for system and network information; aggregates all logs, traps, and debugging information generated by the system and maintains them in order of severity; outputs the network information to multiple channels based on user-defined rules

- Network management

HPE IMC centrally configures, updates, monitors, and troubleshoots

- Remote intelligent mirroring

Mirrors ingress/egress ACL-selected traffic from a switch port or VLAN to a local or remote switch port anywhere on the network

Security

- Access control lists

Provides IP L3 filtering based on source/destination IP, address/subnet, and source/destination TCP/UDP port number

- RADIUS/TACACS+

Eases switch management security administration by using a password authentication server

- Secure shell

Encrypts all transmitted data for secure remote CLI access over IP networks

- IEEE 802.1X and RADIUS network logins Controls port-based access for authentication and accountability

- Port security

Allows access only to specified MAC addresses, which can be learned or specified by the administrator

Convergence

- LLDP-MED (Media Endpoint Discovery)

Defines a standard extension of LLDP that stores values for parameters such as QoS and VLAN to configure network devices such as IP phones automatically

Warranty and support

- For details on Limited Lifetime warranty and software releases available with your product purchase, please refer to hpe.com/networking/support



HPE FlexFabric 5945 Switch Series



Specifications	HPE FlexFabric 5945 32QSFP28 Switch (JQ077A)	HPE FlexFabric 5945 2-slot Switch (JQ075A)
I/O ports and slots	32 x 100 Gb QSFP28 ports 2 x 1 Gb SFP ports	2 module slots 2 x 100 Gb QSFP28 ports Supports up to a maximum of 48 x 10/25GbE and 4 x 100GbE ports, or up to 16 x 100GbE ports from modules
Additional ports and slots	Management ports 1 x console port 1 x mini USB port 1 x USB port 2 x out-of-band management ports (one fiber port and one copper port)	Management ports 1 x console port 1 x mini USB port 1 x USB port 2 x out-of-band management ports (one fiber port and one copper port)
Power supplies	2 power supply slots 1 minimum power supply required (ordered separately)	2 power supply slots 1 minimum power supply required (ordered separately)
Fan tray	5 fan tray slots The customer must order fan trays, as they are not included with the switch. This system requires same-direction airflow fan trays to function properly. The system should not be operated with less than five fan trays for more than 24 hours. The system should not be operated without a fan tray for more than two minutes. The system should not be operated outside of the temperature range of 32°F (0°C) to 113°F (45°C). Failure to comply with these operating requirements may void the product warranty.	5 fan tray slots The customer must order fan trays, as they are not included with the switch. This system requires same-direction airflow fan trays to function properly. The system should not be operated with less than five fan trays for more than 24 hours. The system should not be operated without a fan tray for more than two minutes. The system should not be operated outside of the temperature range of 32°F (0°C) to 113°F (45°C). Failure to comply with these operating requirements may void the product warranty.
Physical characteristics	Dimensions 43.6 x 440 x 460 mm (1.72 x 17.32 x 18.11 in.) Weight ≤10.4 kg (22.93 lb) shipping weight Full configuration weight 10.4 kg (22.93 lb)	Dimensions 44.2 x 440 x 660 mm (1.74 x 17.32 x 25.98 in.) Weight ≤13.1 kg (28.88 lb) shipping weight Full configuration weight 13.1 kg (28.88 lb)
Memory and processor	1 GB flash; packet buffer size: 32 MB, 8 GB SDRAM	1 GB flash; packet buffer size: 32 MB, 8 GB SDRAM
Performance	10 Gbps latency < 1 μs (64-byte packets) Throughput 2024 Mpps Routing/switching capacity 6.4 Tbps Routing table size 324K entries (IPv4), 162K entries (IPv6) MAC address table size 288K entries	< 1 μs (64-byte packets) 2024 Mpps 3.6 Tbps 324K entries (IPv4), 162K entries (IPv6) 288K entries



HPE FlexFabric 5945 Switch Series (continued)

Specifications	HPE FlexFabric 5945 32QSFP28 Switch (JQ077A)	HPE FlexFabric 5945 2-slot Switch (JQ075A)
Reliability MTBF (years)	102	113
Environment Operating temperature Operating relative humidity Acoustic	32°F to 113°F (0°C to 45°C) 5% to 95%, noncondensing Low-speed fan: 62.4 dB, high-speed fan: 78.1 dB	32°F to 113°F (0°C to 45°C) 5% to 95%, noncondensing Low-speed fan: 61.3 dB, high-speed fan: 76.5 dB
Electrical characteristics Frequency Maximum heat dissipation Voltage Maximum power rating Idle power Notes	50/60 Hz 1283 BTU/hr (1458 kJ/hr) 100 VAC to 240 VAC V rated, 90 VAC to 264 VAC max., -40 VDC to -60 VDC rated -40 VDC to -72 VDC max. 650W 154W Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	50/60 Hz 1392 BTU/hr (1458 kJ/hr) 100 VAC to 240 VAC V rated, 90 VAC to 264 VAC max., -40 VDC to -60 VDC rated -40 VDC to -72 VDC max. 650W 136W Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1, CAN/CSA C22.2 No. 60950-1, IEC 60950-1, EN 60950-1, AS/NZS 60950-1, FDA 21 CFR Subchapter J	UL 60950-1, CAN/CSA C22.2 No. 60950-1, IEC 60950-1, EN 60950-1, AS/NZS 60950-1, FDA 21 CFR Subchapter J
Emissions	FCC Part 15 (CFR 47) Class A, ICES-003 Class A, VCCI Class A, CISPR 32 Class A, EN 55032 Class A, AS/NZS CISPR 32 Class A, EN 61000-3-2, EN 61000-3-3, ETSI EN 300 386	FCC Part 15 (CFR 47) Class A, ICES-003 Class A, VCCI Class A, CISPR 32 Class A, EN 55032 Class A, AS/NZS CISPR 32 Class A, EN 61000-3-2, EN 61000-3-3, ETSI EN 300 386
Immunity	CISPR 24, EN 55024, ETSI EN 300 386	CISPR 24, EN 55024, ETSI EN 300 386
Environmental	RoHS compliant	RoHS compliant
Management	IMC; CLI; out-of-band management; SNMP Manager; Telnet; FTP	IMC; CLI; out-of-band management; SNMP Manager; Telnet; FTP
Notes	The customer must install a minimum of one power supply, as the device does not come with one. The customer must install five fan kits, as the device does not come with one.	The customer must install a minimum of one power supply, as the device does not come with one. The customer must install five fan kits, as the device does not come with one.
Services	See the HPE website at hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, contact your local HPE sales office.	See the HPE website at hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, contact your local HPE sales office.



HPE FlexFabric 5945 Switch Series (continued)



Specifications	HPE FlexFabric 5945 48SFP28 8QSFP28 Switch (JQ074A)	HPE FlexFabric 5945 4-slot Switch (JQ076A)
I/O ports and slots	48 x 25 Gb SFP28 ports 8 x 100 Gb QSFP28 ports 2 x 1 Gb SFP ports Supports 48 x 10/25GbE and 8 x 100GbE fixed ports, or up to 80 x 10GbE ports when using splitter cables	4 module slots 2 x 1 Gb SFP ports Supports up to a maximum of 96 x 10/25GbE and 8 x 100GbE ports, or up to 32 x 100GbE ports
Additional ports and slots	1 x console port 1 x mini USB port 1 x USB port 2 x out-of-band management ports (one fiber port and one copper port)	1 x console port 1 x mini USB port 1 x USB port 2 x out-of-band management ports (one fiber port and one copper port)
Power supplies	2 power supply slots 1 minimum power supply required (ordered separately)	4 power supply slots 2 minimum power supplies required (ordered separately)
Fan tray	5 fan tray slots The customer must order fan trays, as they are not included with the switch. This system requires same-direction airflow fan trays to function properly. The system should not be operated with less than five fan trays for more than 24 hours. The system should not be operated without a fan tray for more than two minutes. The system should not be operated outside of the temperature range of 32°F (0°C) to 113°F (45°C). Failure to comply with these operating requirements may void the product warranty.	2 fan tray slots The customer must order fan trays, as they are not included with the switch. This system requires two same-direction airflow fan trays to function properly. The system should not be operated with only one fan tray for more than 24 hours. The system should not be operated without a fan tray for more than two minutes. The system should not be operated outside of the temperature range of 32°F (0°C) to 113°F (45°C). Failure to comply with these operating requirements may void the product warranty.
Physical characteristics		
Dimensions	43.6 x 440 x 460 mm (1.72 x 17.32 x 18.11 in.)	88.1 x 440 x 660 mm (3.47 x 17.32 x 25.98 in.) (2U height)
Weight	10.10 kg (22.27 lb) shipping weight	18.10 kg (39.90 lb) shipping weight
Full configuration weight	15 kg (33.07 lb)	27 kg (59.52 lb)
Memory and processor	1 GB flash; packet buffer size: 32 MB, 8 GB SDRAM	1 GB flash; packet buffer size: 32 MB, 8 GB SDRAM
Performance		
Latency	< 1 μs (64-byte packets)	< 1 μs (64-byte packets)
Throughput	2024 Mpps	2024 Mpps
Routing/switching capacity	4 Tbps	6.4 Tbps
Routing table size	324K entries (IPv4), 162K entries (IPv6)	324K entries (IPv4), 162K entries (IPv6)
MAC address table size	288K entries	288K entries



HPE FlexFabric 5945 Switch Series (continued)

Specifications	HPE FlexFabric 5945 48SFP28 QSFP28 Switch (JQ074A)	HPE FlexFabric 5945 4-slot Switch (JQ076A)
Reliability MTBF (years)	109	113
Environment Operating temperature Operating relative humidity Acoustic	32°F to 113°F (0°C to 45°C) 5% to 95%, noncondensing Low-speed fan: 62.1 dB, high-speed fan: 77.9 dB	32°F to 113°F (0°C to 45°C) 5% to 95%, noncondensing Low-speed fan: 70.8 dB, high-speed fan: 83.2 dB
Electrical characteristics Frequency Maximum heat dissipation Voltage Maximum power rating Idle power Notes	50/60 Hz 1381 BTU/hr (1458 kJ/hr) 100 VAC to 240 VAC V rated, 90 VAC to 264 VAC max., -48 VDC to -60 VDC rated -40 VDC to -72 VDC max. 650W 179W Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	50/60 Hz 2348 BTU/hr (2478 kJ/hr) 100 VAC to 240 VAC V rated, 90 VAC to 264 VAC max., -48 VDC to -60 VDC rated -40 VDC to -72 VDC max. 650W 185W Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1, CAN/CSA C22.2 No. 60950-1, IEC 60950-1, EN 60950-1, AS/NZS 60950-1, FDA 21 CFR Subchapter J	UL 60950-1, CAN/CSA C22.2 No. 60950-1, IEC 60950-1, EN 60950-1, AS/NZS 60950-1, FDA 21 CFR Subchapter J
Emissions	FCC Part 15 (CFR 47) Class A, ICES-003 Class A, VCCI Class A, CISPR 32 Class A, EN 55032 Class A, AS/NZS CISPR 32 Class A, EN 61000-3-2, EN 61000-3-3, ETSI EN 300 386	FCC Part 15 (CFR 47) Class A, ICES-003 Class A, VCCI Class A, CISPR 32 Class A, EN 55032 Class A, AS/NZS CISPR 32 Class A, EN 61000-3-2, EN 61000-3-3, ETSI EN 300 386
Immunity	CISPR 24, EN 55024, ETSI EN 300 386	CISPR 24, EN 55024, ETSI EN 300 386
Management	IMC; CLI; out-of-band management; SNMP Manager; Telnet; FTP	IMC; CLI; out-of-band management; SNMP Manager; Telnet; FTP
Notes	The customer must install a minimum of one power supply, as the device does not come with one. The customer must install five fan kits, as the device does not come with one.	The customer must install a minimum of two power supplies, as the device does not come with one. The customer must install two fan kits, as the device does not come with one.
Services	See the HPE website at hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, contact your local HPE sales office.	See the HPE website at hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, contact your local HPE sales office.



Standards and protocols

Standards and protocols apply to all products in series.

BGP	RFC 1163 BGP RFC 1771 BGPv4 RFC 1997 BGP Communities Attribute	RFC 2918 Route Refresh Capability RFC 3392 Capabilities Advertisement with BGP-4 RFC 4271 A BGP-4	RFC 4360 BGP Extended Communities Attribute RFC 4456 BGP Route Reflection: An alternative to full mesh Internal BGP (IBGP) RFC 4760 Multiprotocol Extensions for BGP-4 RFC 7432 BGP MPLS-Based Ethernet VPN
Device management	RFC 1157 SNMPv1/v2c RFC 1305 NTPv3 RFC 1591 DNS (client) RFC 1902 (SNMPv2)	RFC 1908 (SNMPv1/v2 coexistence) RFC 2573 (SNMPv3 applications) RFC 2576 (coexistence between SNMPv1, v2, v3) RFC 2819 RMON	Multiple configuration files Multiple software images SSHv1/SSHv2 TACACS/TACACS+
General protocols	IEEE 802.1ad Q-in-Q IEEE 802.1AX-2008 Link Aggregation IEEE 802.1D MAC Bridges IEEE 802.1p Priority IEEE 802.1Q VLANs IEEE 802.1s Multiple Spanning Trees IEEE 802.1w Rapid Reconfiguration of Spanning Tree Protocol IEEE 802.3ad Link Aggregation Control Protocol (LACP) IEEE 802.3ae 10-Gigabit Ethernet IEEE 802.3ag Ethernet OAM IEEE 802.3ah Ethernet in First Mile over Point-to-Point Fiber—EFMF IEEE 802.3x Flow Control RFC 768 UDP RFC 783 TFTP Protocol (revision 2) RFC 791 IP RFC 792 ICMP RFC 793 TCP RFC 826 ARP RFC 854 Telnet RFC 856 Telnet RFC 868 Time Protocol RFC 896 Congestion Control in IP/TCP Internetworks RFC 950 Internet Standard Subnetting Procedure RFC 1027 Proxy ARP RFC 1058 RIPv1 RFC 1091 Telnet Terminal-Type Option RFC 1141 Incremental updating of the Internet checksum RFC 1142 OSI IS-IS Intra-domain Routing Protocol RFC 1191 Path MTU discovery	RFC 1213 Management Information Base for Network Management of TCP/IP-based Internet RFC 1253 (OSPFv2) RFC 1531 DHCP RFC 1533 DHCP Options and BOOTP Vendor Extensions RFC 1534 DHCP/BOOTP Interoperation RFC 1541 DHCP RFC 1542 Clarifications and Extensions for the Bootstrap Protocol RFC 1591 DNS (client only) RFC 1624 Incremental Internet Checksum RFC 1723 RIPv2 RFC 1812 IPv4 Routing RFC 2030 Simple Network Time Protocol (SNTP) v4 RFC 2131 DHCP RFC 2236 IGMP Snooping RFC 2338 VRRP RFC 2453 RIPv2 RFC 2581 TCP Congestion Control RFC 2644 Directed Broadcast Control RFC 2767 Dual Stacks IPv4 & IPv6 RFC 2865 RADIUS RFC 2868 RADIUS Attributes for Tunnel Protocol Support RFC 2890 Key and Sequence Number Extensions to GRE RFC 3046 DHCP Relay Agent Information Option RFC 3411 An Architecture for Describing SNMP Management Frameworks RFC 3412 Message Processing and Dispatching for the SNMP	RFC 3413 SNMP Applications RFC 3416 Protocol Operations for SNMP RFC 3417 Transport Mappings for the SNMP RFC 3418 Management Information Base (MIB) for the SNMP RFC 3768 VRRP RFC 4250 The SSH Protocol Assigned Numbers RFC 4251 The SSH Protocol Architecture RFC 4252 The SSH Authentication Protocol RFC 4253 The SSH Transport Layer Protocol RFC 4254 The SSH Connection Protocol RFC 4292 IP Forwarding Table MIB RFC 4293 Management Information Base for the Internet Protocol (IP) RFC 4364 BGP/MPLS IP Virtual Private Networks (VPNs) RFC 4419 Diffie-Hellman Group Exchange for the SSH Transport Layer Protocol RFC 4594 Configuration Guidelines for DiffServ Service Classes RFC 4601 Protocol Independent Multicast—Sparse Mode (PIM-SM): Protocol Specification (Revised) RFC 4604 Using Internet Group Management Protocol Version 3 (IGMPv3) and Multicast Listener Discovery Protocol Version 2 (MLDv2) for Source-Specific Multicast RFC 4607 Source-Specific Multicast for IP RFC 4941 Privacy Extensions for Stateless Address Auto-configuration in IPv6 RFC 5340 OSPF for IPv6 RFC 5905 NTP Version 4: Protocol and Algorithms Specification RFC 2929 RADIUS Support DS for RADIUS
IPv6	RFC 2080 RIPng for IPv6 RFC 2460 IPv6 Specification RFC 2461 IPv6 Neighbor Discovery RFC 2462 IPv6 Stateless Address Auto-configuration RFC 2463 ICMPv6 RFC 2464 Transmission of IPv6 over Ethernet Networks RFC 2473 Generic Packet Tunneling in IPv6 RFC 2545 Use of MP-BGP-4 for IPv6	RFC 2563 ICMPv6 RFC 2711 IPv6 Router Alert Option RFC 2740 OSPFv3 for IPv6 RFC 2767 Dual stacks IPv4 & IPv6 RFC 3315 DHCPv6 (client and relay) RFC 3484 Default Address Selection for IPv6 RFC 3810 Multicast Listener Discovery Version 2 (MLDv2) for IPv6	RFC 4213 Basic Transition Mechanisms for IPv6 Hosts and Routers RFC 4291 IP Version 6 Addressing Architecture RFC 4443 ICMPv6 RFC 4552 Authentication/Confidentiality for OSPFv3 RFC 4862 IPv6 Stateless Address Auto-configuration RFC 5095 Deprecation of Type 0 Routing Headers in IPv6



Standards and protocols (continued)

Standards and protocols apply to all products in series.

MIBs	RFC 1213 MIB II RFC 1907 SNMPv2 MIB RFC 2571 SNMP Framework MIB RFC 2572 SNMP-MPD MIB	RFC 2573 SNMP-Notification MIB RFC 2573 SNMP-Target MIB RFC 2574 SNMP USM MIB RFC 2737 Entity MIB (version 2)	RFC 3414 SNMP-User based-SM MIB RFC 3415 SNMP-View based-ACM MIB LLDP-EXT-DOT1-MIB LLDP-EXT-DOT3-MIB LLDP-MIB
Network management	RFC 2580 Conformance Statements for SMiv2	RFC 3164 BSD syslog Protocol	
OSPF	RFC 1587 OSPF NSSA RFC 2328 OSPFv2 RFC 3101 OSPF NSSA	RFC 3137 OSPF Stub Router Advertisement RFC 3623 Graceful OSPF Restart RFC 4577 OSPF as the Provider/Customer Edge Protocol for BGP/MPLS IP Virtual Private Networks (VPNs)	RFC 4811 OSPF Out-of-Band LSDB Resynchronization RFC 4812 OSPF Restart Signaling RFC 4813 OSPF Link-Local Signaling
QoS/CoS	IEEE 802.1p (CoS) RFC 2475 DiffServ Architecture	RFC 2597 DiffServ Assured Forwarding (AF)	RFC 3247 Supplemental Information for the New Definition of the EF PHB (Expedited Forwarding Per-Hop Behavior) RFC 3260 New Terminology and Clarifications for DiffServ
Security	RFC 1321 The MD5 Message-Digest Algorithm RFC 2818 HTTP Over TLS	RFC 6192 Partial Support—Protecting the router control plane	ACLs SSHv2

New HPE Networking Comware 5945 TAA SKUs

- S3K87A HPE NW CW Sw 48Y 8C TAA 5945 (JQ074A)
- S3K88A HPE NW CW Sw 2-slot TAA 5945 (JQ075A)
- S3K89A HPE NW CW Sw 4-slot TAA 5945 (JQ076A)
- S3K90A HPE NW CW Sw 32C TAA 5945 (JQ077A)

HPE FlexFabric 5945 48SFP28 8QSFP28 Switch (JQ074A) accessories

- HPE 58xOAF 650W AC Power Supply (JC680A)
- HPE FlexFabric Switch 650W 48V Hot Plug NEBS Compliant DC Power Supply (JH336A)
- HPE X712 Back (Power Side) to Front (Port Side) Airflow High Volume 2 Fan Tray (JH389A)
- HPE X711 Front (Port Side) to Back (Power Side) Airflow High Volume 2 Fan Tray (JH388A)

HPE FlexFabric 5945 32QSFP28 Switch (JQ077A) accessories

- HPE 58xOAF 650W AC Power Supply (JC680A)
- HPE FlexFabric Switch 650W 48V Hot Plug NEBS Compliant DC Power Supply (JH336A)
- HPE X712 Back (Power Side) to Front (Port Side) Airflow High Volume 2 Fan Tray (JH389A)
- HPE X711 Front (Port Side) to Back (Power Side) Airflow High Volume 2 Fan Tray (JH388A)

HPE FlexFabric 5945 2-slot Switch (JQ075A) accessories

- HPE 58xOAF 650W AC Power Supply (JC680A)
- HPE FlexFabric Switch 650W 48V Hot Plug NEBS Compliant DC Power Supply (JH336A)
- HPE X712 Back (Power Side) to Front (Port Side) Airflow High Volume 2 Fan Tray (JH389A)
- HPE X711 Front (Port Side) to Back (Power Side) Airflow High Volume 2 Fan Tray (JH388A)



HPE FlexFabric 5945 4-slot Switch (JQ076A) accessories

- HPE 58x0AF 650W AC Power Supply (JC680A)
- HPE FlexFabric Switch 650W 48V Hot Plug NEBS Compliant DC Power Supply (JH336A)
- HPE 5930 4-slot Back (Power Side) to Front (Port Side) Airflow Fan Tray (JH185A)
- HPE 5930 4-slot Front (Port Side) to Back (Power Side) Airflow Fan Tray (JH186A)

HPE FlexFabric 5945 2-slot Switch (JQ075A) and 4-slot Switch (JQ076A) I/O modules

- HPE FlexFabric 5930 24p SFP+ and 2p QSFP+ Module (JH180A)
- HPE FlexFabric 5930 24p SFP+/2p QSFP+ w/Msec Module (JH181)
- HPE FlexFabric 5930 24p 10GBASE-T/2p w/Msec QSFP+ Module (JH182A)
- HPE FlexFabric 5930 8-port QSFP+ Module (JH183A)
- HPE FlexFabric 16-Port 16/32G FC Converged module (JL865A)
- HPE 5930 24p Conv Port and 2p QSFP+ Module (JH184A)
- HPE FlexFabric 5930 24p Conv Port and 2p QSFP+ Module (JH184A)
- HPE FlexFabric 5950 16-port QSFP+ Module (JH405A)
- HPE FlexFabric 5950 8-port QSFP28 Module (JH406A)
- HPE FlexFabric 5950 24-port SFP28 2-port QSFP28 Module (JH450A)
- HPE FlexFabric 5950 8-port QSFP28 MACsec Module (JH957A)

HPE 5945 48SFP28 8QSFP28 Switch (JQ074A), HPE 5945 32QSFP28 Switch (JQ077A), HPE 5945 2-slot Switch (JQ075A), and HPE 5945 4-slot Switch (JQ076A) Optics**Gigabit SFP transceiver modules**

- HPE X120 1G SFP RJ45 T Transceiver (JD089B)
- HPE X120 1G SFP LC SX Transceiver (JD118B)
- HPE X120 1G SFP LC LX Transceiver (JD119B)
- HPE X120 1G SFP LC LH100 Transceiver (JD103A)

Note: 1G transceivers are supported in all Management Ports as well as SFP Ports, SFP+ Ports and SFP28 Ports.

100-Megabit SFP transceiver modules

- HPE X115 100M SFP LC FX Transceiver (JD102B)
- HPE X110 100M SFP LC LX Transceiver (JD120B)

Note: 100M Transceivers are supported **only** in SFP or Management Ports, not in any SFP+ or SFP28 ports.

10-Gigabit SFP+ modules and cables**10-Gigabit SFP+ transceiver modules available for the SFP+ ports and SFP28 ports**

- HPE X130 10G SFP+ LC SR Transceiver (JD092B)
- HPE X130 10G SFP+ LC LR Transceiver (JD094B)
- HPE X130 10G SFP+ LC ER 40km Transceiver (JG234A)
- HPE X130 10G SFP+ LC LH 80km Transceiver (JG915A)
- HPE X130 10G SFP+ LC BiDi 10-U Transceiver (JL737A)
- HPE X130 10G SFP+ LC BiDi 10-D Transceiver (JL738A)
- HPE X130 10G SFP+ LC BiDi 40-U Transceiver (JL739A)
- HPE X130 10G SFP+ LC BiDi 40-D Transceiver (JL740A)
- HPE 32Gb SW Com Temp XCVR (P9H30A)



- HPE 16Gb SFP+ SW 1-pack C Temp XCVR (E7Y10A)
- HPE 16Gb FC/10GbE 100m SFP+ XCVR (H6Z42A)
- HPE 8Gb Short Wave FC SFP+ 1 Pack (AJ718A)
- HPE 32Gb SFP28 SW E Temp 1-pack PT XCVR (Q2P62A)

10-Gigabit SFP+ fiber cables available for the SFP+ ports and SFP28 ports

- HPE X2A0 10G SFP+ to SFP+ 7m Active Optical Cable (JL290A)
- HPE X2A0 10G SFP+ to SFP+ 10m Active Optical Cable (JL291A)
- HPE X2A0 10G SFP+ to SFP+ 20m Active Optical Cable (JL292A)

10-Gigabit SFP+ copper cables available for the SFP+ ports and SFP28 ports

- HPE FlexNetwork X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable (JD095C)
- HPE FlexNetwork X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable (JD096C)
- HPE FlexNetwork X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable (JD097C)
- HPE FlexNetwork X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable (JG081C)

25-Gigabit SFP28 modules and cables**SFP28 transceiver modules available for the SFP28 ports**

- HPE X190 25G SFP28 LC SR 100m MM Transceiver (JL293A)
- HPE 25G SFP28 LC LR 10km SMF Xcvr (JL855A)

SFP28 copper cables available for the SFP28 ports

- HPE X240 25G SFP28 to SFP28 1m Direct Attach Copper Cable (JL294A)
- HPE X240 25G SFP28 to SFP28 3m Direct Attach Copper Cable (JL295A)
- HPE X240 25G SFP28 to SFP28 5m Direct Attach Copper Cable (JL296A)

SFP28 fiber cables available for the SFP28 ports

- HPE X2A0 25G SFP28 to SFP28 3m Active Optical Cable (JH955A)
- HPE X2A0 25G SFP28 to SFP28 5m Active Optical Cable (JH956A)
- HPE X2A0 25G SFP28 to SFP28 7m Active Optical Cable (JL297A)
- HPE X2A0 25G SFP28 to SFP28 10m Active Optical Cable (JL298A)
- HPE X2A0 25G SFP28 to SFP28 20m Active Optical Cable (JL299A)

40-Gigabit QSFP+ modules and cables**QSFP+ transceiver modules available for the QSFP+ and QSFP28 ports**

- HPE X140 40G QSFP+ MPO SR4 Transceiver (JG325B)
- HPE X140 40G QSFP+ MPO MM 850nm CSR4 300m Transceiver (JG709A)
- HPE X140 40G QSFP+ LC BiDi 100m MM Transceiver (JL251A)
- HPE X140 40G QSFP+ LC LR4 SM 10km 1310nm Transceiver (JG661A)
- HPE X140 40G QSFP+ LC LR4L 2km SM Transceiver (JL286A)
- HPE X140 40G QSFP+ LC ER4 40km SM Transceiver (JL306A)

QSFP+ fiber cables available for the QSFP+ and QSFP28 ports

- HPE X2A0 40G QSFP+ to QSFP+ 7m Active Optical Cable (JL287A)
- HPE X2A0 40G QSFP+ to QSFP+ 10m Active Optical Cable (JL288A)
- HPE X2A0 40G QSFP+ to QSFP+ 20m Active Optical Cable (JL289A)
- HPE QSFP/SFP+ Adapter kit (655874-B21)



Data sheet

QSFP+ copper cables available for the QSFP+ and QSFP28 ports

- HPE X240 40G QSFP+ QSFP+ 1m Direct Attach Copper Cable (JG326A)
- HPE X240 40G QSFP+ QSFP+ 3m Direct Attach Copper Cable (JG327A)
- HPE X240 40G QSFP+ QSFP+ 5m Direct Attach Copper Cable (JG328A)

QSFP+ to 4 x SFP+ copper cables available for the QSFP+ and QSFP28 ports

- HPE X240 40G QSFP+ to 4x10G SFP+ 1m Direct Attach Copper Splitter Cable (JG329A)
- HPE X240 40G QSFP+ to 4x10G SFP+ 3m Direct Attach Copper Splitter Cable (JG330A)
- HPE X240 40G QSFP+ to 4x10G SFP+ 5m Direct Attach Copper Splitter Cable (JG331A)

100-Gigabit QSFP28 modules and cables

QSFP28 transceiver modules available for the QSFP28 ports

- HPE X150 100G QSFP28 MPO SR4 100m MM Transceiver (JL274A)
- HPE X150 100G QSFP28 LC BiDi 100m MM Transceiver (JQ344A)
- HPE X150 100G QSFP28 MPO PSM4 500m SM Transceiver (JH420A)
- HPE X150 100G QSFP28 LC LR4 10km SM Transceiver (JL275A)
- HPE X150 100G QSFP28 CWDM4 2km SM Transceiver (JH673A)
- HPE X150 100G QSFP28 SWDM4 100m MM Transceiver (JH419A)
- HPE X150 100G QSFP28 eSR4 300m MM Transceiver (JH672A)

QSFP28 fiber cables available for the QSFP28 ports

- HPE X2A0 100G QSFP28 to QSFP28 7m Active Optical Cable (JL276A)
- HPE X2A0 100G QSFP28 to QSFP28 10m Active Optical Cable (JL277A)
- HPE X2A0 100G QSFP28 to QSFP28 20m Active Optical Cable (JL278A)

QSFP28 copper cables available for the QSFP28 ports

- HPE X240 100G QSFP28 to QSFP28 1m Direct Attach Copper Cable (JL271A)
- HPE X240 100G QSFP28 to QSFP28 3m Direct Attach Copper Cable (JL272A)
- HPE X240 100G QSFP28 to QSFP28 5m Direct Attach Copper Cable (JL273A)

QSFP28 to SFP28 copper cables available for the QSFP28 ports

- HPE X240 QSFP28 4xSFP28 1m Direct Attach Copper Cable (JL282A)
- HPE X240 QSFP28 4xSFP28 3m Direct Attach Copper Cable (JL283A)
- HPE X240 QSFP28 4xSFP28 5m Direct Attach Copper Cable (JL284A)

Learn more at
[HPE.com/networking](https://www.hpe.com/networking)

Visit **HPE GreenLake**



Chat now (sales)


**Hewlett Packard
Enterprise**

© Copyright 2024 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

VMware vSAN is a registered trademark or trademark of VMware, Inc. and its subsidiaries in the United States and other jurisdictions. sFlow is a registered trademark of InMon Corp. All third-party marks are property of their respective owners.

a00049249ENW, Rev. 1.3